



WORLD TAPES

adhesive and safety solutions

WORLD TAPES S.L.

Avda Touroperador, Bungalow Las Carrozas n. 1, Campo Internacional (Maspalomas)

CP 35100 San Bartolomé de Tirajana, Las Palmas España - info@worldtapes.es - www.worldtapes.es

Technical data sheet

WT- 8931B D/S black PE foam tape

Issue date: 05/6/2012

Edition: 1

Authorized:

DIMENSIONS:

Thickness: 1 mm
Roll widths from: 4 a 1050 mm

SPECIFICATIONS:

Adhesive: modified solvent acrylic
Carrier: Black polyethylene foam
Liner: blue PE 80 my
Density: 67 kg/m³
Peel adhesion: 23 +/- 2 N/25mm
(PSTC 1)
Temperature resistance: - 40° + 120°C

APPLICATIONS:

Advised on photovoltaic system, mirrors, glass, panels, plates, plastic materials, profiles. Resistant against plasticizers, solvents and UV rays. HIGH – COESION ADHESIVE PROPERTIES

Available in spool wound roll form in different widths 4 to 19 mm lengths.

The above performance features are based on the results of tests and careful calculations. They are put forward in good faith but are not guaranteed. The enduser should check the suitability of the product for its intended use and consult us for any doubt about particular applications. Storage should be in dry, well ventilated rooms with a temperature around 20°C and protected from continuous exposure to direct sunlight. Always apply the product to clean and dry surfaces.