



# WORLD TAPES

adhesive and safety solutions

## WORLD TAPES S.L.

Avda Touroperador, Bungalow Las Carrozas n. 1, Campo Internacional (Maspalomas)

CP 35100 San Bartolomé de Tirajana, Las Palmas España - [info@worldtapes.es](mailto:info@worldtapes.es) - [www.worldtapes.es](http://www.worldtapes.es)

---

*Technical data sheet*

## **WT-AG80** D/S grey acrylic foam tape

*Issue date: 05/6/2012*

---

*Edition: 1*

---

*Authorized:*

---

### **DIMENSIONS:**

**Thickness:** 0,8 mm  
**Roll widths from:** 4 a 1000 mm

### **SPECIFICATIONS:**

**Adhesive:** solvent acrylic  
**Carrier:** grey acrylic foam  
**Liner:** red PE  
**Peel adhesion:** 8 +/- 2 N/25mm  
**Tensile strength:** 10,5 kg/cm<sup>2</sup>  
**Elongation at break:** >850%  
**Temperature resistance:** - 30° + 150°C

### **APPLICATIONS:**

Advised on many surfaces, replaces admirably screws and rivets. Excellent resistance to temperature, plasticizers, oils, solvents and UV rays

---

The above performance features are based on the results of tests and careful calculations. They are put forward in good faith but are not guaranteed. The enduser should check the suitability of the product for its intended use and consult us for any doubt about particular applications. Storage should be in dry, well ventilated rooms with a temperature around 20°C and protected from continuous exposure to direct sunlight. Always apply the product to clean and dry surfaces.