



WORLD TAPES

adhesive and safety solutions

WORLD TAPES S.L.

Avda Touroperador, Bungalow Las Carrozas n. 1, Campo Internacional (Maspalomas)

CP 35100 San Bartolomé de Tirajana, Las Palmas España - info@worldtapes.es - www.worldtapes.es

Technical data sheet

WT- AT40 D/S transparent acrylic foam tape

Issue date: 05/6/2012

Edition: 1

Authorized:

DIMENSIONS:

Thickness: 0,4 mm
Roll widths from: 4 a 1000 mm

SPECIFICATIONS:

Adhesive: solvent acrylic
Carrier: transparent acrylic foam
Liner: red PE
Peel adhesion: 7 +/- 2 N/25mm
Tensile strength: 12 kg/cm²
Elongation at break: >900%
Temperature resistance: - 30° + 150°C

APPLICATIONS:

Advised on many surfaces, replaces admirably screws and rivets. Excellent resistance to temperature, plasticizers, oils, solvents and UV rays. Particularly advised for assembling transparent surfaces.

The above performance features are based on the results of tests and careful calculations. They are put forward in good faith but are not guaranteed. The enduser should check the suitability of the product for its intended use and consult us for any doubt about particular applications. Storage should be in dry, well ventilated rooms with a temperature around 20°C and protected from continuous exposure to direct sunlight. Always apply the product to clean and dry surfaces.